



- 1) Todos os postes deverão ser aterrados adequadamente.
- 2) Os cabos unipolares serão de cobre isolados para 0,6/1KV.
- 3) Os dutos subterrâneos serão do tipo corrugado, em PEAD 2 1/2".
- 4) Todo pavimento danificado com a passagem de dutos, retirada de poste, caixas de passagem, etc., deverão ser recompostos imediatamente .
- 5) Tudo aquilo que aqui não estiver especificado, deverá atender as normas pertinentes e vigentes da CELESC e ABNT.
- 6) O quadro de medição, instalado à 3 m de altura no poste, deverá ser provido de lente inclinada para leitura da CELESC.



* VALORES COM BASE : PROJETO LED 400W / LUMINÁRIA LED 265W

QD MEDIÇÃO	FASE	PROJETOR LED 400W	LUMINÁRIA LED 265W	TOTAL (W)	TOTAL (QD) (W)
		QTD/TOT. (W)	QTD/TOT. (W)		
01	A	12 / 4800	4 / 1060	5860	16115
	B	12 / 4800	4 / 1060	5860	
	C	09 / 3600	3 / 795	4395	
02	A	12 / 4800	4 / 1060	5860	17580
	B	12 / 4800	4 / 1060	5860	
	C	12 / 4800	4 / 1060	5860	
03	A	12 / 4800	4 / 1060	5860	17580
	B	12 / 4800	4 / 1060	5860	
	C	12 / 4800	4 / 1060	5860	
04	A	12 / 4800	4 / 1060	5860	17580
	B	12 / 4800	4 / 1060	5860	
	C	12 / 4800	4 / 1060	5860	
05	A	12 / 4800	4 / 1060	5860	17580
	B	12 / 4800	4 / 1060	5860	
	C	12 / 4800	4 / 1060	5860	
06	A	06 / 2400	2 / 530	2930	8790
	B	06 / 2400	2 / 530	2930	
	C	06 / 2400	2 / 530	2930	

The image displays two technical drawings of street lighting models, labeled 'Avenida' and 'Paseo', showing side and front views with dimensions.

Model Avenida (Left):

- Side View (Top):** Shows a curved arm with a height of 12.000. The arm has a horizontal span of 3.500 and a vertical offset of 1.000.
- Front View (Bottom):** Shows the base with a height of 12.000. The base is labeled 'AVENIDA' and 'PASEO' with arrows indicating the direction of the arm.

Model Paseo (Right):

- Side View (Top):** Shows a curved arm with a height of 12.000. The arm has a horizontal span of 3.500 and a vertical offset of 1.000. A secondary arm is shown with a height of 8.000 and a horizontal span of 1.000.
- Front View (Bottom):** Shows the base with a height of 12.000. The base is labeled 'AVENIDA' and 'PASEO' with arrows indicating the direction of the arm.

Technical drawing of a street lighting pole assembly, showing side and front views with dimensions and labels.

Labels:

- LUMINÁRIA LED A SER INSTALADA
- PROJETOR LED A SER INSTALADO
- JANELA DE INSPEÇÃO
- LIXEIRA SOLTA
- LIXEIRA SOLDADA NO POSTE
- ESPESURA CHAPA METÁLICA 2mm

Dimensions (mm):

- 1.200
- 0.400
- Ø 0.090
- 0.400
- 0.350
- 2.500
- 0.500
- 3.500
- 0.150
- 10.000
- 4.000
- 0.050
- 0.400
- 0.090
- 0.350
- 0.115
- Ø 15cm

